



- Gamme FAW BESTUNE PASSENGER CARS
- Gamme FAW -Tiger
- Gamme FAW J6P Tractor Truck 420HP





**Gamme FAW - BESTUNE PASSENGER CARS** 

**FAW GROUP** 

#### **T77 PRO**





#### Specification

#### **Engine and Transmission**

Displacement (L)	1.5	
Rated Power (Km/rpm)	124/5,500	
Rated Torque (Nm/rpm)	258/1,500-4,350	
Transmission Type	6MT/7DCT	

#### **DIMENSION**

Exterior	Overall Length (mm)	4,525
	Overall Width (mm)	1,845
	Overall Height (mm)	1,615
	Wheelbase (mm)	2,700
Weight	Curb Mass (Kg)	1,468/1,515

#### **T90**

Powertrain		
Engine	Petrol	
	1.5 L turbo 14	
	2.0 L turbo 14	
Transmission	8-speed automatic	

Dime	ensions
Wheelbase	2,772 mm (109.1 in)
Length	4,718 mm (185.7 in)
Width	1,880 mm (74.0 in)
Height	1,710 mm (67.3 in)



#### **T99**





#### Specification

**Engine and Transmission** 

Displacement (L)	2.0
Rated Power (Km/rpm)	165
Max. Torque (N m)	340
Transmission Type	8AT

#### **DIMENSION**

Exterior	Overall Length (mm)	4800
	Overall Width (mm)	1915
	Overall Height (mm)	1685
	Wheelbase (mm)	2870
	Front Wheeltread (mm)	1640
	Rear Wheeltread (mm)	1640
Weight	Curb Mass (Kg)	1775
Tires		245/50 R20

#### **B70**





#### **SPECIFICATION**

#### **Engine and Transmission**

Engine Label (L)	CA4GD1	CA4GC18T
Displacement (mL)	1,999	1,796
Max. Power (kW)	108	137
Max. Torque (Nm)	184	235
Transmission Type	6-speed manual-auto all-in-one transmission	

#### **Fuel Consumption**

Fuel Type	Gasoline
Fuel Tank Capacity (L)	58
Fuel Consumption (Combined) (liter/100km)	7.6

#### **Dimension**

Exterior	Overall Length (mm)	4,800
	Overall Width (mm)	1,820
	Overall Height (mm)	1,472
	Wheelbase (mm)	2,725
	Front Wheeltread (mm)	1,550
	Rear Wheeltread (mm)	1,550
Cargo	Cargo Volume (L)	522
Weight	Curb Mass (Kg)	1,480
	Heaviest Curb Weight (kg)	1,930

#### NAT - EV





#### **SPECIFICATION**

Basic parameters	FAW Bestune NAT
Manufacturer	FAW Bestune
Classification	Compact MPV
Energy type	Pure Electric
Time to market	2023.03
All-electric range (km)	425
Fast charging time (hours)	0.5
Fast charge percentage	80
Maximum power (kw)	100
Maximum torque (n * m)	260
Motor (Ps)	136
Length, width and height (mm)	4450*1840*1680
Body structure	5 doors 5 seats MPV
Maximum speed (km / h)	140
0-100km/h Acceleration time (s)	10.8
Wheelbase (mm)	2850
Front track width (mm)	1595
Rear track width (mm)	1569
Full load minimum ground clearance (mm)	117
Trunk Capacity (PCs.)	454
Curb weight (kg)	1700
Battery type	Lithium iron phosphate
Front tire specification	215/55 R17
Rear tire specification	215/55 R17





Gamme FAW -Tiger



#### **Tiger VR** Single Row 4X2 E2 2.3L 109HP Narrow Cabin GVW≤5T



☐ Working conditions recommended: supermarket (township), agricultural and sideline products transportation (agricultural market, catch-up), individual business, logistics park freight rental, building materials home

□ Common speed: 50-70km/h

□ Payload: 2.5T

☐ Transport distance: Short distance 50-100km

☐ Option: Yunnei490QZL Engine/ 2800mm Wheelbase

Model	CA1040P40K50EA84
Engine	WP2.3NQ110E20
Gearbox	WLY-MG85B
Front Axle	DR052
Rear Axle	130 Welding axle Speed ratio 4.33/5.125
Suspension	3/7+3
Wheelbase	2500mm
Frame	760*150*60*4 mm
Cabin	Tiger VR single-row cab, Electric doors and windows + Central control lock, A/C, Multi-function Steering Wheel
Tire	7.00R16-P14
Other	Double Coin Tire, 80L Iron Tank, Comi ABS, Clearance Self-Regulation, Liquid Brake, Rear Protection, Rear Single Tire

Commercial Vehicle Overseas Sales Company--Algeria Branch (Europe, Middle East and North Africa)



#### **Tiger VR** Single Row 4X2 E2 2.7L 109HP Narrow Cabin GVW≤5T



☐ Working conditions recommended: supermarket (township),
agricultural and sideline products transportation (agricultural
market, catch-up), individual business, logistics park freight
rental, building materials home

□ Common speed: 50-70km/h

□ Payload: 3-4T

☐ Transport distance: Short distance 50-100km

Model	CA1041P40K50EA84
Engine	Yunnei 490QZL
Gearbox	WLY-MG85
Front Axle	DR052
Rear Axle	130 Welding axle Speed ratio 5.125
Suspension	3/7+3
Wheelbase	3300mm
Frame	760*150*60*4 mm
Cabin	Tiger VR single-row cab, A/C+ Electric doors and windows + Central control lock, Full package interior, Frame rearview mirror
Tire	6.50R16-P10
Other	Auxiliary Light, 80L Iron Fuel Tank, ABS, Liquid Brake, Mechanical Brake

Commercial Vehicle Overseas Sales Company--Algeria Branch (Europe, Middle East and North Africa)



#### **Tiger VN** Single Row 4X2 E2 2L 120HP Medium Cabin GVW≤5T



☐ Working conditions recommended: supermarket (township), agricultural and sideline products transportation (agricultural market, catch-up), individual business, logistics park freight rental, building materials home

□ Common Speed: 50-70km/h

□ Payload: 3-4T

☐ Transport distance: short distance 50-100km

Model	CA5047XXYP40K50L1EA84-3		
Engine	Yunnei D25TCI		
Gearbox	WLY-6TS40		
Front Axle	DD030		
Rear Axle	1058 Welding axle Speed ratio 4.875		
Suspension	3/7+3		
Wheelbase	3300mm		
Frame	780*180*65*5 mm		
Cabin	Tiger VR single-row cab, A/C		
Tire	7.0R16 P12		
Other	70L Plastic Fuel Tank, Constant Speed Cruise, 780 Wide Frame, Break Brakes, With Guide Cover		



#### **Tiger VH** Single Row 4X2 E2 3.0L 119HP Wide Cabin GVW≤7T



Working conditions recommended: efficient logistics, fruit and		
vegetable transportation, high-end customer cold chain ( medicine,		
dairy products, frozen fresh transportation, etc.)		

□ Common speed: 90-110km/h

□ Payload: 3-5T

☐ Transport distance: More than 300km

Model	CA1061P40K2L2EA85	
Engine	YC4D130-33	
Gearbox	WLY-6TS115	
Front Axle	D135	
Rear Axle	1068 stamping welding axle Speed ratio 5.375	
Suspension	7/10+3	
Wheelbase	3560mm	
Frame	795-216*75*6	
Cabin	Tiger VH Half row cab, A/C	
Tire	7.5R16-P14	
Other	Air Brake, Soft Shaft, Strengthened Leaf Spring, 110 L Iron Fuel Tank, Electric Doors and Windows + Central Control Lock, With Guide Cover	



#### **Tiger VH** Single Row 4X2 E2 4.0L 129HP Wide Cabin GVW≤9T



<b>□</b> Working conditions recommended : efficient logistics, fruit a				
	vegetable transportation, high-end customer cold chain ( medicine,			
	dairy products, frozen fresh transportation, etc. )			

☐ Common speed: 90-110km/h

☐ Payload: 3-6T

☐ Transport distance: More than 300km

Model	CA1083P40K2L1EYA84	
Engine	YC4D130-33	
Gearbox	WLY6T115/6TS40/6TS115	
Front Axle	7B9	
Rear Axle	1069 stamping welding axle Speed ratio 5.375	
Suspension	3/10+4	
Wheelbase	3300	
Frame	865*216*75*6mm	
Cabin	Tiger VH single row cab, A/C	
Tire	7.50R16 P14	
Other	Other Maintenance-free battery, 100L Iron Fuel Tank, Air Brake	



#### **Tiger VH** Single and Half Row 4X2 E2 4.0L 129HP Wide Cabin GVW≤11T



☐ Working conditions recommended: efficient logistics, fruit and vegetable transportation, high-end customer cold chain (medicine, dairy products, frozen fresh transportation, etc.)

□ Common speed: 90-110km/h

□ Payload: 7-8T

☐ Transport distance: More than 300km

□ Cargo Body 6200\*2300\*2300

Model	CA1110P40K2L5EA85	
Engine	YC4D130-33	
Gearbox	WLY6TS55	
Front Axle	X141B	
	1080 Cast axle	
Rear Axle	Speed ratio 5.286	
Suspension	7/10+4	
Wheelbase	4700mm	
Frame	865*216*75*6 mm	
Cabin	Tiger VH flat top half row cab, electric doors and windows + central control lock, A/C	
Tire	8.25R16	
Other	Double Coin Tire, Brake with Air Breaking, Exhaust Brake, 100L Iron Tank, Free Maintenance Battery, Rear Protection, Strengthen Shock Absorber.	

Commercial Vehicle Overseas Sales Company--Algeria Branch (Europe, Middle East and North Africa)



#### **Tiger V Series Configuration Reference Euro Ⅲ**

	Tiger VR 4X2	er VR 4X2 Tiger VN 4X2		Tiger VH 4X2				
PAYLOAD	1-3t	3-5t	3-5t	6-12t				
GVW	≤5t	≤7t	≤7t	≤16t				
ENGINE	CA4DB1-11/13E3 CA 2.5L-E3-2023	Cummins ISF2.8s3129T  CA 2.5L-E3-2023  Yunnei D25TC1	Cummins ISF2.8s3129T	Cummins ISF3.8s3141/154 YC4D130-33				
GEARBOX	WLYMG85B	WLY6TS40	WLY15-35/6TS115	WLY6TS55/FAST8TS75TC				
REAR AXLE	130 stamping welding axle	130/1058 stamping welding axle	1058/1069stamping welding axle	1068/1080 stamping welding axle 435Cast Steel				
FRONT AXLE	DR052-1.5T	DR600/DD030-3T	7B9/D135/X349	X349/X141-4.5T				
FRAME	760*150*60*4	780*180*65*5	865*216*75*6	795*216*75*6/ 865*250*65*(8+5)				
SUSPENSION	3/3+2 3/7+3	3/7+3 3/7+9	3/3+3 3/7+9	7/10+4				
TIRE	650/205/75R16/6.5R16/7.0R16	6.5R16 7.0R16	215(235)/75R17.5	8.25(9.00)R20				
Commercial Vehicle Overseas Sales CompanyAlgeria Branch (Europe, Middle East and North Africa)								





**Gamme FAW - J6P Tractor Truck 420HP** 



## Model

### CA4180P66K2E

Tractor Head-Euro 3 - 4X2 - 420HP

Recommend areas:

Algeria ning condition

Running conditions:

Full-load  $\leq 49t$ 

Selling points:

Safety, Reliable, Comfortable, Powerful, Longlife, Lower fuel consumption, Lower center of gravity



# PARAMETERS

## MASS DATA (in kg)

Combination GVW Weight 18000

Curb Weight of Vehicle 7000

Pemissible Max.Axle Load F/R 7000/13000

Manufactures Axle Load F/R 7000/13000

## DIMENSIONS (in mm)

 Length (mm)
 6150

 Width (mm)
 2500

 Height (mm)
 3560

 Wheel Base
 3800

 Overhang(Chassis)
 F&R
 1495&1050

 Wheel Track
 F&R
 2020&1830

## PERFORMANCE

Max. Speed (km/h) 87

Max. Grade Ability (%) 29

Approach Angle (°) 17

Departure Angle (°) 40

Parking Brake Grade Angle (%) 20

Min. Ground Clearance (mm) 222

Min. Steering Diameter (m) 15

Fuel Consumption (L/100km) 31.4
Fuel Tank Capacity (L) 600

## STRUCTURES

## CAB

Category

J6P Flat Roof/Row and a Half/4 Points-Full Floating LCD Instrument Panel, Electric Glass, Manual Rear-view Mirror, Trailer Brake, Ventilation Seat for Driver

## MISCELLANEOUS

Auto AC, 4 Points Air Suspension, 600L Fuel Tank, Aluminum Radiator, Aluminium Alloy Air Reservoir, Front Protection Device, Electrc--Hydraulic Lifting, Overall anti-splashing Mud Baffle, PTO

# SPECIAL EQUIPMENT

ABS, Dual Circuit Air Braking System, Cruise Control, 90km/h Speed Limiter, Front and Side Guard Device, Headrest and 3-point Belt per Seat, Vehicle Traveling Data Recorder, Defogging Device

# CONFIGURATION

### BIGINE

Model CA6DM2-42

Type 6 in-line/Water-cooling/Four stroke/Inter-

cooling/Direct injection

Displacement (L) 11.04

Max Output Power (Kw/rpm) 312/1900

Max Torque (Nm/(r/min)) 1900/1200-1500

Emission Level EURO III

## TRANSMISSION

Model FAST 12JSD200T-B

Type Overdrive/Synchronizer/

Twin countershaft

Forward Shifts Ratio i1=15.53,i2=12.22,i3=9.39,i4=7.33,i5=5.73,i6=4 .46,i7=3.48,i8=2.74,i9=2.10,i10=1.64,i11=1.28,i

12=1.00

Reverse Shifts Ratio iRH=3.33,iRL=14.86

## CLUTCH

Model & Type Pull type diaphragm clutch

Driven Plate Dia. φ430

### STERING

Model

Type Recycle ball-type power steering gear

Ratio 23

### REARAXIE

Model & Type 7T-498 Cast steel wheel reduction

Reduction Ratio 4.444

### FRAME

Structures Side rails/punching/riveted

Rail Section (mm) 300\*80\*(8+5)

# SUSPENSION

Suspension Type Balance Suspension

Front Suspension Size 3

Rear Suspension Size 3+3

### BRAKE

Driving Brake Dual circuit air braking system

Parking Brake Manual valve spring cylinder storage brake

Auxiliary Brake Exhaust brake

## 

Rim 9.00×22.5

Tire Model 11R22.5-18PR

Tire Type Radial/Tubeless

### 

Type

Jost

Construction Drop-forged heat treated steel

Mounting Outboard-mounted raised mounting plate

Kingpin size φ50

CHINA FAW GROUP IMPORT & EXPORT CO., LTD. - Algeria Branch (Europe, Middle East, North Africa)



#### Model

#### CA4250P66K24TIAIEX

Tractor Head-Euro 3 - 6X4 - 420HP

Recommend areas:

Algeria

Running conditions:

Full-load  $\leq 70 t$ 

Selling points:

Safety, Reliable, Comfortable, Powerful, Longlife,

Lower fuel consumption, Lower center of gravity



# PARAMETERS

## MASS DATA (in kg)

Combination GVW Weight 25000

Curb Weight of Vehicle 9900 (Estimated)

Pemissible Max.Axle Load F/R 9000/16000\*2

Manufactures Axle Load F/R 9000/32000

## DIMENSIONS (in mm)

Length (mm) 6915 Width (mm) 2500 Height (mm) 3850 Wheel Base 3400+1350 Overhang(Chassis) F&R 1495&770 Wheel Track F&R 2020&1830

# PERFORMANCE

Max. Speed (km/h) 77 Max. Grade Ability (%) 33 Approach Angle (°) Departure Angle (°) 40 20 Parking Brake Grade Angle (%) Min. Ground Clearance (mm) 222 Min. Steering Diameter (m)

Fuel Consumption (L/100km) 31.4 Fuel Tank Capacity (L) 600

# STRUCTURES

## CAB

Category

J6P Flat Roof/Row and a Half/2 Points-Full Floating LCD Instrument Panel, Eletric Glass, Eletric Rear-view Mirror, Trailer Brake, Air Seat for Driver

## MISCELLANEOUS

Auto AC, Rear-2 Points Air Suspension, 400L Iron Fuel Tank, Iron Bumper, Manual--Hydraulic Lifting, Integrated Iron Shell Oil Bath Air Filter and Aluminum Radiator, Maintenance-Free Batteries 150AH, Simple Mud Baffle, Desert Air Filter, PTO

# SPECIAL EQUIPMENT

ABS, Dual Circuit Air Braking System, Cruise Control, 90km/h Speed Limiter, Front and Side Guard Device, Headrest and 3-point Belt per Seat, Vehicle Traveling Data Recorder, Defogging Device

# CONFIGURATION

### BNGNB

CA6DM2-42E3 Model

6 in-line/Water-cooling/Four stroke/Inter-Type

cooling/Direct injection

Displacement (L) 11.04 312/1900 Max Output Power (Kw/rpm) Max Torque (Nm/(r/min)) 1900/1200-1500 **Emission Level** EURO III

# TRANSMISSION

CA12TAX210M Model

Overdrive/Synchronizer/ Type Twin countershaft

Forward Shifts Ratio i1=15.53,i2=12.22,i3=9.39,i4=7.33,i5=5.73,i6=4

.46,i7=3.48,i8=2.74,i9=2.10,i10=1.64,i11=1.28,i

12 = 1.00

Reverse Shifts Ratio iRH=3.33,iRL=14.86

#### CLUTCH

Model & Type Pull type diaphragm clutch

Driven Plate Dia. ф430

## SIBBRING

Model **TRW** 

Recycle ball-type power steering gear Type

Ratio

### REARAXIE

300 Hub cast steel wheel reduction Model & Type

Reduction Ratio 5.921

### RAMB

Side rails/punching/riveted Structures

300×80×8+8 Rail Section (mm)

## SUSPENSION

Double I rods rear balance suspension Suspension Type

Front Suspension Size 12

Rear Suspension Size 12

### BRAKE

Dual Crcuit Air Braking System **Driving Brake** 

Parking Brake Manual valve spring cylinder storage brake

**Auxiliary Brake** Exhaust brake

## 

 $9.00 \times 20$ Rim Tire Model 12R20-18PR Radial/Tubeless Tire Type

### 

Jost Type

Drop-forged heat treated steel Construction

Outboard-mounted raised mounting plate Mounting

Kingpin size φ90

CHINA FAW GROUP IMPORT & EXPORT CO., LTD. - Algeria Branch (Europe, Middle East, North Africa)